



An ISO 9001:2000 company

OXXIDES, INC.

3 Kearney Avenue
Harriman, NY 10926

Tel: 845 238 5142 Fax 845 238 5143
e-mail: oxxides@oxxides.com

SPECIFICATION

ANTIMONY TRIOXIDE

MASTER BATCH : GRANULATED GUARANTEED TECHNICAL DATA:

ANTIMONY TRIOXIDE	Sb ₂ O ₃	92.0% MIN.
ARSENIC OXIDE	As ₂ O ₃	0.06% MAX.
LEAD	Pb	0.08% MAX.
IRON	Fe	0.04% MAX.
TIN	Sn	0.008%MAX.
COPPER	Cu	0.002%MAX.
SULFUR	S	0.001%MAX.
SPECIFIC GRAVITY		3.17
BINDER (DOP)		6 TO 7%
COLOR:		WHITE
SHELF LIFE:		5 YEARS MIN.
CONTAMINATION:	PRODUCT IS FREE FROM FOREIGN MATERIAL IN KEEPING WITH GOOD RUBBER AND PLASTICS PRACTICES.	

DUST FREE

*MASTER BATCH GRANULATED ANTIMONY TRIOXIDE SUPPLIED BY OXXIDES, INC.
COMES IN 25KG CARTONS, SHRINK -WRAPPED AND PALLETIZED.

APPLICATIONS:

THE MAJOR USE OF ANTIMONY TRIOXIDE IS AS A FLAME RETARDANT SYNERGIST IN PLASTICS, RUBBER, POLYURETHANES (A FLEXIBLE & RIGID FOAM), TEXTILES, ADHESIVES, FIBERGLASS, & PAPER.

GLASS MANUFACTURERS USE IT AS A FINING AGENT OR AS A DEGASSER (TO REMOVE BUBBLES).

RAYON MANUFACTURERS AS WELL AS OIL REFINERIES USE AS ANTIMONY OXIDE AS A CATALYST.

PORCELAIN AND ENAMELING SERVICES USE IT AS AN OPACIFIER.

PAINT MANUFACTURERS USE ANTIMONY OXIDE AS A WHITE PIGMENT.

IT IS SOMETIMES USED WITH OTHER MATERIALS TO FORM YELLOW PIGMENTS.

* IF MSDS IS REQUIRED, PLEASE CALL OXXIDES, INC. TEL. 845 238 5142

** ANTIMONY TRIOXIDE IS NOT A HAZMAT REGULATED PRODUCT IN 25 KG CARTONS

CAS NO. 1309-64-4
U.N. NO. 9201

n